

# HexaByte

Connecting the dots

---

## GPS | Real Time Tracker



# Performances

- \*Plug and play
- \*Support specified protocols
- \*Real-time speed report
- \*Battery voltage alarm
- \*Smart power on/off
- \*Power off alarm
- \*Real-time tracking
- \*Tow alarm
- \*Direction variation trace
- \*ACC detection
- \*Geo-Fence
- \*Speed limits alarm
- \*Smart power saving
- \*SMS report with google map link
- \*Smart sleep mode
- \*Theft alarm
- \*Vibration alarm
- \*Distance interval trace

## SPECIFICATION

Hardware	Dimension	78.5(63)*47*26.5mm
	Power Supply	DC 6V~36V
	GSM Frequency	Quad band (850M/900M/1800M/1900M)
	Built-in Battery Capacity	280mAh/3.7V
Firmware	Trace Records in GSM Blind Area	4000 points
	FOTA Protocol	TCP
	USSD Protocol	Embodied
GPS	GPS Accuracy	<15m
	A-GPS Accuracy	<100m
	GPS Sensitivity	-162dBm
	Startup Time	Hot start<3S, warm start<15S, cool start<60S
	Frequency	1575MHz
	Display Information	Longitude, Latitude, Hight, Speed
Environment	Operation Temperature	-20°C ~ 65°C (-4°F ~ 149°F)
	Operation Humidity	10% ~ 80% (Non-Condensing)
	Storage Temperature	-30°C ~ 80°C (-22°F ~ 176°F)
	Storage Humidity	0% ~ 90% (Non-Condensing)
Product list	Device	1 pc (Standard)
	Power Supply Extension Line	1 pc (Optional accessory)